



# BODY 940 SEALANT

Technical Data Sheet No 716

Elastomer -based, water- and sound-proof material

## General Technical Description

Specially formulated sealing material for lights, glass and joints in the car body

The sealant retains its elasticity with time and exhibits exceptional endurance in temperature fluctuations

Good mechanical and chemical resistance

## Surface

It is also suitable for filling cracks between joints, metalconcrete and concrete-concrete.

## Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL/BODY 771 ANTISIL FAST..

Make sure the surface is air dried rather than wiped dry



Make sure you always use appropriate face protection and good ventilation

## Product Application:

»» It is also special for joints filling, metal - beton and beton - betonite is not recoatable. It CAN NOT be painted. It is easily applied with a cartridge



Always close tin after use

**Flash Point:**  
58°C / 48°F

**Specific Gravity:**  
1.51 g/cm<sup>3</sup>

**Solid Content (No thinner):**  
78% Weight

### VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 280 g/L.  
2004/42/II B(e)(840)280

### Theoretical Coverage:

-

### Cleaning of equipment:

Clean after final use with Body 740 ACRYL NORMAL/BODY 767 EXTRA NITRO THINNER

### Remarks:

- Allow for additional time for combi spray booths to reach the desired temperature
- Best results when used with HB BODY PRODUCTS
- It can be used by countries that do not adopt the VOC legislation as well.

### Storage shelf life:

- Store in a cool place (+5°C - +25°C) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers



Apply with brush or with the cartridge



Protect from humidity



Fast drying



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The SPECIAL REFINISHING PRODUCT. 1K ACRYLIC MAT PRODUCT intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2015, November 2015